GSIB1505 THRU GSIB15100

SINGLE PHASE
GLASS PASSIVATED BRIDGE RECTIFIER
Voltage: 50 to 1000V **Current: 15.0A**

GULF SEMI

Features

Glass passivated chip junction
Ideal for printed circuit board
High surge current capability
High case dielectric strength
This series is UL listed under Recognized Component Index, file number E330278

Mechanical Data

Terminal: Plated leads solderable per MIL-STD 750, Method 2026
Case: UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: Polarity symbol marked on body
Mounting position: any

GSIB-5S



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half -wave, 60Hz, resistive or inductive load rating at 25℃, unless otherwise stated)

	Symbol	GSIB 1505	GSIB 1510	GSIB 1520	GSIB 1540	GSIB 1560	GSIB 1580	GSIB 15100	units
Maximum repetitive peak reverse voltage	Vrrm	50	100	200	400	600	800	1000	V
Maximum RMS voltage	Vrms	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	Vdc	50	100	200	400	600	800	1000	V
Maximum average forward Rectified output current at Tc = 107℃(Note 1) Ta = 25℃(Note 2)	If(av)	15.0 3.5							A
Peak forward surge current single sine-wave superimposed on rated load (JEDEC Method)	Ifsm	300							A
Maximum instantaneous forward voltage drop per leg at 7.5A	Vf	1.0							V
Rating for fusing (t < 8.3ms)	I^2t	240							A^2Sec
Maximum DC reverse current at rated DC blocking voltage per leg Ta = 25℃ Ta = 125℃	Ir	10.0 250							μA
Maximum thermal resistance per leg (Note2) (Note1)	Rth(ja) Rth(jc)	22.0 1.5							℃/W
Operating junction and storage temperature range	Tj, Tstg	-55 to +150							℃

Note:
1. Unit case mounted on Al plate heatsink
2. Unit case mounted on P.C.B. without heatsink
3. Recommended mounting position is to bolt down on heatsink with silicone thermal compound for maximum heat transfer with #6 screw



Figure 1. Derating Curve Output Rectified Current



Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Leg



Figure 3. Typical Forward Characteristics Per Leg



Figure 4. Typical Reverse Characteristics Per Leg



Figure 5. Typical Junction Capacitance Per Leg



Figure 6. Typical Transient Thermal Impedance